


**ELGEF Plus Transition coupler PE/stainless steel
d20-63mm / SDR11 / Male thread R**



- **PE 100 SDR 11** (ISO S5)
- 10 bar Gas / 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Supplied as a kit



d	Thread Type	Size	DN	PN	Code	Weight	Do	Lmax	P1	SLW	SDR pipe
(mm)		(inch)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	
20	R	½	15	16	724 920 756	0.165	31	110	34	30	9-11
25	R	¾	20	16	724 920 757	0.249	36	111	34	35	9-11
32	R	1	25	16	724 920 758	0.332	44	117	34	40	9-11
40	R	1 ¼	32	16	724 920 759	0.464	54	127	39	50	9-11
50	R	1 ½	40	16	724 920 760	0.611	66	135	43	60	9-11
63	R	2	50	16	724 920 761	0.942	81	147	46	70	9-17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>